



NO	PARAMETER	VALUE						
1	Model	T2 Max	T2R Max 2+16G	T2R Max 1+16G	T6 Max	X1 Android	X1 Same Screen	X1 mini
2	Projection Technology	LCD Full Closed Optical Machine	LCD Full Closed Optical Machine	LCD Full Closed Optical Machine	LCD Full Closed Optical Machine	Single LCD	Single LCD	Single LCD
3	Lens	Full Glass Lens	Full Glass Lens	Full Glass Lens	Full Glass Lens	Full Glass Lens	Full Glass Lens	Full Glass Lens
4	Light Source	LED	LED	LED	LED	LED	LED	LED
5	Brightness (ANSI)	250 Ansilms	350 Ansilms	350 Ansilms	650 Ansilms	350 Ansilms	350 Ansilms	200 Ansilms
6	Resolution	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080	720 P / 1080 P Optional	1280 X 720	Support 1080 P
7	Contrast	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	1500:1
8	Input Interface	HDMI*1 / USB*1 / 3.5mm / AV*1 / DC*1	HDMI*1 / USB*1 / 3.5mm*1 / DC*1	HDMI*1 / USB*1 / 3.5mm*1 / DC*1	HDMI*1 / USB*2 / 3.5mm*1 / AV*1 / DC*1	HDMI*1 / USB*1 / 3.5mm*1 / AV*1 / DC*1	HDMI*1 / USB*1 / 3.5mm*1 / AV*1 / DC*1	HDMI*1 / USB*1 / 3.5mm*1 / AV*1
9	Lamp Life (Hours)	20,000	20,000	20,000	20,000	20,000	20,000	20,000
10	Projection Scale	4:3 / 16:9	4:3 / 16:9	4:3 / 16:9	4:3 / 16:9	4:3 / 16:9	4:3 / 16:9	4:3 / 16:9
11	Keystone Correction	Four Directional Keystone Correction Automatic - Up and Down	Four Directional Keystone Correction Automatic - Up and Down	Four Directional Keystone Correction Automatic - Up and Down	Four Directional Keystone Correction Automatic - Up and Down	Four Directional Keystone Correction Automatic - Up and Down	Manually - Up and Down	NO
12	Scaling Function	Support	Support	Support	Support	Support	-	-
13	Proposed Projection Distance (m)	1.2 - 3.0	1.2 - 3.0	1.2 - 3.0	1.35 - 3.5	1.25 - 2.5	1.25 - 2.5	1.0 - 2.0
14	Proposed Projection Screen Size (inch)	50 - 120	50 - 120	50 - 120	60 - 150	50 - 120	50 - 120	40 - 100
15	Support System	Android 9.0	Android 9.0	Android 9.0	Android 9.0	Android 9.0	Multimedia System + Wifi Moduel Same Screen: Iphone - Wire / Wireless; Android - DLAN Projection	Multimedia System
16	Memory	1G + 16G	2G + 16G	1G + 16G	2G + 16G	1G + 8G	NO	NO
17	Chip	MTK 9269	Amlogic T972	MTK 9269	Amlogic T972	MTK 9269	-	-
18	CPU	4*A53	4*A55	4*A53	4*A55	4*A53	-	-
19	Wi-Fi	2.4G	2.4G + 5G	2.4G	2.4G + 5G	2.4G	2.4G	NO
20	Bluetooth	4.0	5.0	4.0	5.0	4.0	-	-
21	Focus	Manual	Manual	Manual	Auto-Focus	Manual	Manual	Manual
22	Remote Control	Infrared Remote Control	Bluetooth Voice	Infrared Remote Control	Bluetooth Voice	Infrared / Can be updated to Bluetooth V.4.0	Infrared Remote Control	Infrared Remote Control
23	Support Languages	Multi-Language	Multi-Language	Multi-Language	Multi-Language	Multi-Language	Multi-Language	Multi-Language
24	Input Voltage (V)	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz	110V - 240V (±10%), 50-60Hz
25	Power (W)	55 W	55 W	55 W	120 W	65 W	65 W	34 W
26	Adapter	19V 3A	19V 3A	19V 3A	19V 6.32A	-	-	15V 2.4A
27	Speakers	3W X 2	3W X 2	3W X 2	5W X 2 (Independent Digital Power Amplifier)	3W X 1	3W X 1	3W X 1
28	Standard Accessories	User Manual, Adapter, Remote control	User Manual, Adapter, Remote control	User Manual, Adapter, Remote control	User Manual, Adapter, Remote control	User Manual, Remote control, AC Line	User Manual, Remote control, AC Line	User Manual, Adapter, Remote control
29	Certificate	CCC, CE, FCC, ROHS	CCC, CE, FCC, ROHS	CCC, CE, FCC, ROHS	CCC, CE, FCC, ROHS, PSE	CCC, CE, FCC, ROHS, SRRC, PSE	CCC, CE, FCC, ROHS, SRRC, PSE	CE
30	Intelligent Cooling Control	Yes	Yes	Yes	Yes	-	-	-
31	Heat-Triggered Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
32	Front Infrared Receiver	Yes	Yes	Yes	Yes	Yes	Yes	Yes
33	Color	White	White - Blue	White	White	White	White	Yellow
34	Net Weight (Kg)	0.9	0.9	0.9	1.935	1.23	1.23	0.616
35	GW (Kg) / (Including Accessories)	1.47	1.47	1.47	2.78 / 2.73 Optional	1.69	1.69	0.965
36	Product Size (L*W*H) mm	110*140*150 mm	110*135*165 mm	110*135*165 mm	137*195*201 mm	220*185*80 mm	220*185*80 mm	165*122*86 mm
37	Colour Box Size (L*W*H) mm	184*150*235 mm	184*150*235 mm	184*150*235 mm	240*236*218 mm	255*220*155 mm	255*220*155 mm	229*204*103 mm
38	Carton Box 1Set (L*W*H)	165*200*255 mm / 1.633 Kgs	165*200*255 mm / 1.633 Kgs	165*200*255 mm / 1.633 Kgs	251*251*236 mm / 3.175 / 3.125 Optional	270*235*175 mm / 1.96 Kgs	270*235*175 mm / 1.96 Kgs	240*212*116 mm / 1.16 Kgs
39	Carton Box 8 Sets (L*W*H)	420*355*535 mm / 13.92 Kgs	420*355*535 mm / 13.92 Kgs	420*355*535 mm / 13.92 Kgs	528*523*266 mm / 13.7 / 13.5 Optional (4 Sets)	560*495*387 mm / 16.97 Kgs	560*495*387 mm / 16.97 Kgs	594*500*228 mm / 12.49 Kgs (10 Sets)
					Inverted Stereo Box			
					Support Car Power Supply with 12V Input			